

Magnus NF 5W30

Description

A fuel economy, synthetic, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- mid SAPS content
- suitable for modern catalysts and DPF filters
- a fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

This universal, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters (DPF). Due to its special composition it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III.

Performance Level

ACEA C3, API SP, VW 504.00/507.00, MB-29.31/229.51/229.52, BMW Longlife-04, Porsche C30

Typicals

Density at 15 °C, kg/l	0,850
Viscosity -30 °C, mPa.s	5050
Viscosity 40 °C, mm²/s	68,80
Viscosity 100 °C, mm²/s	12,20
Viscosity Index	179
Flash Point COC, °C	220
Pour Point, °C	-42
Total Base Number, mgKOH/g	8.3
Sulphate Ash, %	0,75