



## Ventus Multisynth 10W40

<b>Description</b>	<p>This universal motor oil is produced with special base oils that have a natural high viscosity index, to which additives are added to obtain the following properties:</p> <ul style="list-style-type: none"> <li>- a high and stable viscosity index</li> <li>- a fast cold start</li> <li>- a strong resistance against oxidation</li> <li>- a safe lubrication film at high temperature</li> <li>- a good detergency and dispersion</li> <li>- a strong protection against wear, corrosion and foaming</li> </ul>	
<b>Application</b>	<p>A universal motor oil, recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.</p>	
<b>Specifications</b>	<p>Performance level            ACEA A3/B3, A3/B4-08            API SL/CF            MB 229.1            VW 501.01/505.00</p>	
<b>Typicals</b>	<p>Density at 15 °C, kg/l            Viscosity -25 °C, mPa.s            Viscosity 40 °C, mm<sup>2</sup>/s            Viscosity 100 °C, mm<sup>2</sup>/s            Viscosity Index            Flash Point COC, °C            Pour Point, °C            Total Base Number, mgKOH/g            Sulphate Ash, %</p>	<p>0,867            6000            92,00            13,80            153            232            -39            8,3            1,08</p>