

Photon Specialsynth NF 5W40

Description	<p>A universal synthetic motor oil, developed according the most recent technology and based on specially selected synthetic base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained:</p> <ul style="list-style-type: none"> - a high and very stable viscosity index - a high resistance against shearing - a fast cold start - a safe lubrication film at very high temperatures - reduced formation of combustion ashes - a very good detergency and dispersion - a very strong protection against wear, corrosion and foaming 	
Application	<p>This universal synthetic motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. Moreover this lubricant is also very suitable for passenger car diesel engines with pump-injector-unit. This product meets the requirements of several OEM's and thus has a wide application.</p>	
Performance Level	<p>ACEA C3 API SN/CF BMW Longlife-04 MB-Approval 229.51 Approved under VW 505.00/505.01 Meets the requirements of GM dexos 2 Porsche A40</p>	
Typicals	<p>Density at 15 °C, kg/l Viscosity -30 °C, mPa.s Viscosity 40 °C, mm²/s Viscosity 100 °C, mm²/s Viscosity Index Flash Point COC, °C Pour Point, °C Total Base Number, mgKOH/g Sulphate Ash, %</p>	<p>0,850 5760 74,80 13,20 180 224 -36 7,4 0,78</p>