

Perfectus NF 5W30

Description	 A fuel economy, synthetic, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties: a lower fuel consumption mid SAPS content suitable for modern catalysts and DPF filters a fast cold start a safe lubrication film at high temperatures extended oil drain intervals a very good detergency and dispersion a very strong protection against wear, corrosion and foaming 	
Application	This universal, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo- charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters (DPF). Due to its special composition it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III.	
Performance Level	ACEA C3, API SP, Approved under VW 504.00/507.00, MB-Approval 29.31/229.51/229.52, BMW Longlife-04, Porsche C30	
Typicals	Density at 15 °C, kg/l Viscosity -30 °C, mPa.s Viscosity 40 °C, mm²/s Viscosity 100 °C, mm²/s Viscosity Index Flash Point COC, °C Pour Point, °C Total Base Number, mgKOH/g Sulphate Ash, %	0,852 5980 69,80 12,30 176 224 -42 8.3 0,75