



## Premium Turbo 15W40

### Description

This is a multigrade engine oil, formulated with a special selection of high quality solvent refined and hydrotreated base stocks and a performance additive package to ensure conformance with the requirements of API CF/CD/SF performance levels. It is intended for application in older models of heavy-loaded, naturally aspirated or turbocharged diesel engines operating at variable conditions and a wide temperature range in commercial trucks, buses, farm and construction equipment and machines. It can also be used in gasoline engines whose manufacturers prescribe the application of API SF performance level lubricants. It has the following benefits:

- Engine cleanliness,
- Thermal and oxidation stability,
- Stable lubricating film

### Application

This multigrade engine oil can be used in older models of heavy-loaded, naturally aspirated or turbocharged diesel engines operating at variable conditions and a wide temperature range in commercial trucks as well as in gasoline engines whose manufacturers prescribe the application of API SF performance level lubricants

### Performance Level

API CF/CD/SF, MB 227.1

### Typicals

Density at 15 °C, kg/l	0,880
Viscosity 40 °C, mm <sup>2</sup> /s	106.4
Viscosity 100 °C, mm <sup>2</sup> /s	14.5
Viscosity Index	140
Flash Point COC, °C	228
Pour Point, °C	-31
Total Base Number, mgKOH/g	9.0
Sulphate Ash, %	1.25