

Premium Turbo Extra 20W50

Description

This is a multigrade engine oil, formulated with a special selection of high quality solvent refined and hydrotreated base stocks and a performance additive package to ensure conformance with the requirements of API CF/CD/SF performance levels. It is intended for application in older models of heavy-loaded, naturally aspirated or turbocharged diesel engines operating at variable conditions and a wide temperature range in commercial trucks, buses, farm and construction equipment and machines. It can also be used in gasoline engines whose manufacturers prescribe the application of API SF performance level lubricants. It has the following benefits:

- Engine cleanliness,
- -Thermal and oxidation stability,
- -Stable lubricating film

Application

This multigrade engine oil can be used in older models of heavy-loaded, naturally aspirated or turbocharged diesel engines operating at variable conditions and a wide temperature range in commercial trucks as well as in gasoline engines whose manufacturers prescribe the application of API SF performance level lubricants

Performance Level

API CF/CD/SF, MB 227.1

Typicals

Density at 15 °C, kg/l	0,888
Viscosity 40 °C, mm ² /s	168.4
Viscosity 100 °C, mm²/s	19.0
Viscosity Index	128
Flash Point COC, °C	236
Pour Point, °C	-23
Total Base Number, mgKOH/g	9.0
Sulphate Ash, %	1.25