

## Quark Multitrac 15W40

<b>Description</b>	<p>An up-to-date multifunctional lubricating oil for agricultural- and earthmoving equipment, formulated with top-grade solvent refined base oils and additives, to achieve the following properties:</p> <ul style="list-style-type: none"> <li>- a powerful dispersion and detergency</li> <li>- a high activity against wear, corrosion and foam</li> <li>- a very strong resistance to oxidation</li> <li>- an excellent extreme pressure properties</li> <li>- a high and stable viscosity index</li> </ul>	
<b>Application</b>	<p>This multifunctional lubricant (*) has been developed to achieve one single lubricating oil that is able to lubricate:</p> <ul style="list-style-type: none"> <li>- gasoline engines</li> <li>- diesel engines (with or without turbo-charging)</li> <li>- transmissions (also "wet" brakes)</li> <li>- hydraulic systems</li> </ul> <p>(*) a so-called <i>Super Tractor Oil Universal = STOU</i></p>	
<b>Performance Level</b>	<p>Performance level            API SF/CG-4/GL-4            ACEA E3, MIL-L-2104D            John Deere J27            Massey Ferguson CMS M1144/M1145            MB 227.1            ZF TE-ML 06B/07B            Allison C4            Cat TO-2            Ford M2C134-D            John Deere J20C            Massey Ferguson CMS M1143</p>	
<b>Typicals</b>	<p>Density at 15 °C, kg/l            Viscosity -20 °C, mPa.s            Viscosity 40 °C, mm<sup>2</sup>/s            Viscosity 100 °C, mm<sup>2</sup>/s            Viscosity Index            Flash Point COC, °C            Pour Point, °C            Total Base Number, mgKOH/g            Sulphate Ash, %</p>	<p>0,874            4760            93,50            14,50            137            218            -30            11,3            1,57</p>