



Fortis Unifleet Ultra 15W40

Description A gasoline- and diesel engine oil, formulated with solvent refined base oils and a well-balanced choice of additives. This engine oil has the following properties:

- a very powerful detergency prevents deposits in the engine
- a very strong dispersion that prevents from precipitation and sludge
- a powerful activity against corrosion and foam
- a high and stable viscosity index
- a low sulphated ash number
- a powerful activity against wear resulting in strongly reduced wear of piston-rings and cylinder-liners

Application This engine lubricant is applicable to gasoline and diesel engines (normally- or turbo-aspirated) even under tough operation conditions and all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved. This product is suitable for application in Euro 4 and Euro 5 engines.

Performance Level ACEA E7
 API CI-4/SL
 MB-Approval 228.3
 Mack EO-N, Renault VI RLD-2
 Volvo VDS-3
 Meets the requirements of
 Cat ECF-1-a/ECF-2
 Cummins CES 20077/20078
 Detroit Diesel 93K215
 Deutz DQC III-10
 Global DHD-1
 JASO DH-1
 Mack EO-M Plus
 MAN M 3275-1
 MTU Type 2

Typicals	Density at 15 °C, kg/l	0,875
	Viscosity -20 °C, mPa.s	6730
	Viscosity 40 °C, mm ² /s	110,50
	Viscosity 100 °C, mm ² /s	14,60
	Viscosity Index	136
	Flash Point COC, °C	228
	Pour Point, °C	-36
	Total Base Number, mgKOH/g	11,1
	Sulphate Ash, %	1,43