

Gamma Super Gear Oil GL-5 85W140

Description	<p>This gear oil is a mineral lubricating oil for mechanical transmissions, formulated with high quality solvent refined base oils and special EP-additives to obtain the following properties:</p> <ul style="list-style-type: none">- excellent resistance against oxidation- a very high activity against wear, corrosion and foam- a low pour point- very good EP-properties												
Application	<p>This gear oil is used in hypoid differentials under very heavy duty conditions and should be used in all transmissions that require EP-transmission oils.</p>												
Performance Level	<p>Performance level API GL-5 MIL-L-2105D ZF TE-ML 07A/21A</p>												
Typicals	<table><tr><td>Density at 15 °C, kg/l</td><td>0,909</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>340,00</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>27,00</td></tr><tr><td>Viscosity Index</td><td>106</td></tr><tr><td>Flash Point COC, °C</td><td>245</td></tr><tr><td>Pour Point, °C</td><td>-15</td></tr></table>	Density at 15 °C, kg/l	0,909	Viscosity 40 °C, mm ² /s	340,00	Viscosity 100 °C, mm ² /s	27,00	Viscosity Index	106	Flash Point COC, °C	245	Pour Point, °C	-15
Density at 15 °C, kg/l	0,909												
Viscosity 40 °C, mm ² /s	340,00												
Viscosity 100 °C, mm ² /s	27,00												
Viscosity Index	106												
Flash Point COC, °C	245												
Pour Point, °C	-15												