

## Gamma Super Gear Oil HS GL-5, 75W90

<b>Description</b>	<p>This gear oil is a semi-synthetic lubricating oil for mechanical transmissions, formulated with high quality solvent refined and synthetic base oils and special EP-additives to obtain the following properties:</p> <ul style="list-style-type: none"><li>- excellent resistance against oxidation</li><li>- a very high activity against wear, corrosion and foam</li><li>- a low pour point</li><li>- very good EP-properties</li><li>- fuel economy</li></ul>												
<b>Application</b>	<p>This gear oil is used in hypoid differentials under very heavy duty conditions and should be used in all transmissions that require EP-transmission oils.</p>												
<b>Performance Level</b>	<p>Performance level API GL-5 MIL-L-2105D ZF TE-ML 07A/17B</p>												
<b>Typicals</b>	<table><tr><td>Density at 15 °C, kg/l</td><td>0,867</td></tr><tr><td>Viscosity 40 °C, mm<sup>2</sup>/s</td><td>80,90</td></tr><tr><td>Viscosity 100 °C, mm<sup>2</sup>/s</td><td>14,80</td></tr><tr><td>Viscosity Index</td><td>192</td></tr><tr><td>Flash Point COC, °C</td><td>190</td></tr><tr><td>Pour Point, °C</td><td>-45</td></tr></table>	Density at 15 °C, kg/l	0,867	Viscosity 40 °C, mm <sup>2</sup> /s	80,90	Viscosity 100 °C, mm <sup>2</sup> /s	14,80	Viscosity Index	192	Flash Point COC, °C	190	Pour Point, °C	-45
Density at 15 °C, kg/l	0,867												
Viscosity 40 °C, mm <sup>2</sup> /s	80,90												
Viscosity 100 °C, mm <sup>2</sup> /s	14,80												
Viscosity Index	192												
Flash Point COC, °C	190												
Pour Point, °C	-45												