

## Gamma Gear Oil MT/LD GL-4 75W80

|                          |   |   |
|--------------------------|---|---|
| <b>Description</b>       | <p>This gear oil is a synthetic lubricating oil for mechanical transmissions, formulated with high quality synthetic base oils and special EP-additives to obtain the following properties:</p> <ul style="list-style-type: none"> <li>- an excellent thermal stability</li> <li>- a very high activity against wear, corrosion and foam</li> <li>- a low pour point</li> <li>- very high quality EP-properties</li> <li>- good clutch-switch performance at low temperatures</li> <li>- long durability</li> <li>- fuel economy</li> </ul> |   |
| <b>Application</b>       | <p>This gear oil is special developed for gearboxes under very heavy duty conditions together with high temperatures. This oil can also be used for extended drain intervals.</p>   |   |
| <b>Performance Level</b> | <p>API GL-4<br/>           MAN 341 Typ Z4<br/>           ZF TE-ML 01L/02L/16K<br/>           Meets the requirements of<br/>           DAF<br/>           Eaton Europe (extended drain)<br/>           Iveco<br/>           Renault<br/>           Volvo 97307<br/>           ZF TE-ML 08/13</p>   |   |
| <b>Typicals</b>          | <p>Density at 15 °C, kg/l<br/>           Viscosity 40 °C, mm<sup>2</sup>/s<br/>           Viscosity 100 °C, mm<sup>2</sup>/s<br/>           Viscosity Index<br/>           Flash Point COC, °C<br/>           Pour Point, °C</p>  | <p>0,858<br/>           59,50<br/>           10,00<br/>           155<br/>           218<br/>           -45</p> |