

ATF 8G

Description	<p>A very high graded automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives to obtain the following properties:</p> <ul style="list-style-type: none"> - important contribution fuel economy - excellent lubrication - very good resistance against oxidation and a very high thermal stability - excellent and very stable friction characteristics that enable longer oil-replacement intervals - excellent resistance against foaming - excellent protection against wear - a very high and stable viscosity index - green coloured 	
Application	<p>This premium synthetic product is specially formulated for the lubrication of ZF 8HP transmissions. This oil contributes greatly to realizing fuel saving and can be used amongst others in the ZF 8HP transmissions 8HP45, 8HP55, 8HP70 and 8HP90. It can also be used in certain ZF 6HP transmissions, which are used in various VAG models.</p>	
Performance Level	<p>Performance level BMW 8322 2152426/2289720(ATF3+) Chrysler 68157995AA Fiat 9.55550-AV5 Jaguar 02JDE 26444 Land Rover LR023288 VAG G-060-162</p>	
Typicals	<p>Density at 15 °C, kg/l Viscosity 40 °C, mm²/s Viscosity 100 °C, mm²/s Viscosity Index Flash Point COC, °C Pour Point, °C</p>	<p>0,842 25,80 6,00 190 198 -45</p>