

Ignitus NF 5W30

Description	A universal, synthetic fuel economy motor oil developed according the most recent technology and based on specially selected synthetic base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained: - a lower fuel consumption - a high and very stable viscosity index - a high resistance against shearing - a fast cold start - a safe lubrication film at very high temperatures - reduced formation of combustion ashes - a very good detergency and dispersion - a very strong protection against wear, corrosion and foaming	
Application	This universal, fuel saving synthetic motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. Moreover this lubricant is also very suitable for passenger car diesel engines with pump-injector-unit. This product meets the requirements of several OEM's and thus has a wide application.	
Performance Level	ACEA C3 API SN MB-Approval 229.51/229.52 Approved under VW 505.00/505.01 GM Dexos 2 BMW Longlife-04	
Typicals	Density at 15 °C, kg/l	0,850
	Viscosity -30 °C, mPa.s	6000
	Viscosity 40 °C, mm ² /s	72,60
	Viscosity 100 °C, mm ² /s	12,30
	Viscosity Index	168
	Flash Point COC, °C	230
	Pour Point, °C	-36
	Total Base Number, mgKOH/g	7,4
	Sulphate Ash, %	0,78